

PINWOODFER

Copyright © 2019-2023 SubDude Audio LLC, Idaho, USA. All Rights Reserved. Reproduction, transmission or redistribution of this document or its contents without written permission is prohibited.

Take your time, follow the instructions, relax, and enjoy yourself!


WARNINGS: Perform installation with your pinball machine turned off and unplugged from AC power.



PinWoofers JJP Tweeter Instructions

Locate Factory Tweeter Quick Connectors

- Remove the backglass.
- Locate the Factory Tweeter Connectors.
- They are typically tucked away behind the mid-range speaker magnets.



PiNWOODFER

Disconnect Factory Tweeters

- Decouple the tweeter connectors.
- There is one connector on the right, and one on the left.
- Pull only on the connectors and not the wires.



PiNWOODFER

Remove Speaker Panel

- The speaker panel will be secured by two Torx Head Machine Screws.
- These may require either a T-15 or T-20 Torx Bit (varies).
- These may also be security Torx Bits.
- Torx Bits may be available at your hardware store, or online.
- Remove the two screws that hold the Speaker Panel in place.
- Use your free hand to support the panel so it does not fall or scratch the backbox sides.



PINWOOFER

Remove Factory Tweeters from Speaker Panel


- There are four Phillips head screws securing each tweeter to the speaker panel.
- Remove all screws and discard the Factory Tweeters.



PiNWOOFER

View of Factory Speaker Panel


- For reference, the top of the panel has the narrower edge.



PiNWOODFER

Install New Tweeters

- Add your new tweeters as shown, re-using the original screws.
- It is vital that you install the new tweeters in the orientation shown. Otherwise, the backglass may be obstructed and you will be unable to lock it back into place.



PINWOOFER

Bottom Hole Marker

- Please note that there is a bottom hole maker on the tweeter for reference.



PINWOOFER

Re-Install Speaker Panel

- Feed the new tweeter wires through the openings behind the speaker panel.
- Secure the mounting screws as shown



PiNWOODFER

Re-Connect Tweeters

- Re-connect the two tweeter connectors and tuck them away behind the speaker magnets as shown.



PINWOOFER

FINWOODSER

End of Document